

Product	Total transfer tamper evident material (Easy Release)
Liner	Glassine paper white, 100gsm
Backing	Matt polyester film 0.045mm
Adhesive	Acrylic resin, pressure sensitive
Description	This material will leave a message on the surface as well as in the film when attempted to be removed, thus providing unmistakable evidence of tampering. A variety of colours and custom design void messages are available on request. The material surface is suitable for various printing methods. Also suitable for fibrous surfaces including paper and cardboard.
Typical applications	Suitable for HSE surfaces, material will leave permanent residue
Application temperature	18°C – 25°C (R.H.55% ±5%)

Total Thickness	0.11mm		
Temperature resistance	-30°C ~ 80°C		
Initial Tack (PSTC-6 #14 ball)	< 10 cm		
Holding Power (PSTC-7)	> 24 hrs 0.5kg/2.5cmx2.5cm		
Peel strength 180° (PSTC-1)	<180 g/2.5cm		
Peel strength 90° (PSTC-1)	g/2.5cm	OZ/in	N/2.5cm
	<250	<6.35	<1.76

For best result apply with pressure at room temperature on a clean surface and allow some time for reaching optimal bond strength.

The 'x' in the code represents the colour. Standard colours are:

0=Black, 1=Light Blue, 2=Red, 3=Green, 4=Yellow, 5=Silver, 6=Purple, 8=White, 9=Dark red, 10=Orange